

Description

Treadmaster TM3 is a synthetic rubber bonded cork material, it has a high degree of resistance to oil and grease and is suitable for most indoor and outdoor uses. It exhibits high coefficient of friction properties and gives many years of service when used in high usage areas such as buses and buildings.

Fire Properties

Property	Test Method	Result
Surface Spread of Flame	BS476-7	Class 2

Physical Properties

Property	Test Method	Result
Sheet Size (max)	Width / Length	1.0 x 6.1m
Hardness, °IRHD	ISO 48	75°
Density, g/cm ³	ISO 2781	1.50
Tensile Strength, MPa	ASTM F152	3.5
Flexibility	ASTM F147	3d
Abrasion Resistance	Taber Abrader 3000 cycles, 500g	Weight loss 0.5g Thickness loss 0.2mm
Slip Resistance	TRRL Pendulum	Dry 81 Wet 36
Residual Indentation	BS EN 12104	4.5%

Information in this document and otherwise supplied to users is based on our general experiences and is given in good faith but, because of particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or implied with respect to such information. Specifications are subject to change without notice. Statements of operating limits quoted in this document are not an indication that these values can be simultaneously applied. A safe handling data sheet on this material is available on request.